



**SPECIFICATIONS**

- For return lines to reservoir
- Sizes from 3/4" (-12) to 4" (-64) in carbon steel
- Convenient companion flange as reservoir outlet connection
- Internal NPT thread as mounting point for strainer or baffle tube
- Contains bolt patterns for both inch (SAE J518) and metric (ISO 6162)
- Additional sizes, jump sizes, thread types and material available upon request

**GENERAL DIMENSIONS**

PART NUMBER	Ø A	B	Ø C	D	Ø E	F NPTF THREAD	UNC 1	UNC 2	G TAP	M 1	M 2	H TAP
ARC-12NPT-12	2.75	1.625	2.625	.500	.750	¾ - 14	.875	1.875	3/8-16 UNC - 2B	.875	1.875	M10X1.5 - 6H
ARC-16NPT-16	3.000	1.625	2.875	.500	1.000	1 - 11.5	1.031	2.062	3/8-16 UNC - 2B	1.031	2.062	M10X1.5 - 6H
ARC-20NPT-20	3.250	1.750	3.125	.500	1.250	1 ¼ - 11.5	1.188	2.312	7/16-14 UNC - 2B	1.188	2.312	M10X1.5 - 6H
ARC-24NPT-24	3.750	1.875	3.625	.500	1.500	1 ½ - 11.5	1.406	2.750	1/2-13 UNC - 2B	1.406	2.750	M12X1.75 - 6H
ARC-32NPT-32	4.500	1.875	4.375	.500	2.000	2 - 11.5	1.688	3.062	1/2-13 UNC - 2B	1.688	3.062	M12X1.75 - 6H
ARC-40NPT-40	5.000	1.875	4.875	.500	2.500	2 ½ - 8	2.000	3.500	1/2-13 UNC - 2B	2.000	3.500	M12X1.75 - 6H
ARC-48NPT-48	6.000	2.000	5.875	.500	3.000	3 - 8	2.438	4.188	5/8-11 UNC - 2B	2.438	4.188	M16X2 - 6H
ARC-64NPT-64	7.000	2.000	6.875	.500	4.000	4 - 8	3.062	5.125	5/8-11 UNC - 2B	3.062	5.125	M16X2 - 6H

\*Dimensions are inches